




The HST-610L-R Pro offers brand-new automatic barrier gates equipped with telescopic boom arm that allows direction exchanging according to site application and a silvery housing with built-in LED indicating the state of the parking barrier, providing humanized user experience.

Features

- ✓ Auxiliary traffic lights in the main body
- ✓ Support anti-smash automatic closing
- ✓ Opening and closing angle of 90° ±2°
- ✓ Opening time:0.8 s Material:1.5mm
- ✓ Over 5 million times Arm
- ✓ Protection Class : IP55 weather proof

Dimensions





The cabinet on the left



Model	CV-610L 3 sec 6M	CV-610R 3 sec 6M	CV-610L 0.8 sec 4M	CV-610R 0.8 sec 4M
Arm	Max 6 m	Max 6 m	Max 4 m	Max 4 m
control	Left	Right	Left	Right
Voltage	AC110V/220V,	AC110V/220V,	AC110V/220V,	AC110V/220V,
Consumption	Power:120W	Power:120W	Power:120W	Power:120W
Remote	≤30m	≤30m	≤30m	≤30m
Material	:1.5mm stainless	:1.5mm stainless	:1.5mm stainless	:1.5mm stainless
Temperature	:-35 to 75 degree	:-35 to 75 degree	:-35 to 75 degree	:-35 to 75 degree
Size	380*390*1010mm	380*390*1010mm	380*390*1010mm	380*390*1010mm
Protection	Class:IP55	Class:IP55	Class:IP55	Class:IP55
speed	:1400rpm	:1400rpm	:1400rpm	:1400rpm
Net Weight	45kg	45kg	45kg	45kg





www.hlogicgroup.com